



## Permanent split capacitor motor 3,3" (85 x 85 mm). For refrigeration, extraction and ventilation.

### Features

- \* Permanent split capacitor motor / 4 poles
- \* 1625 R.P.M
- \* Volts 115 - 127 - 220 - 240 - 277 480 VAC
- \* Sealed ball bearing (-45°C to +150°C)
- \* Ball bearing lifetime up to 100.000 hours
- \* Aluminium endshields
- \* Silent operation
- \* Totally enclosed
- \* Thermal protection
- \* Other models / specifications available upon request
- \* Multi speeds
- \* Multiple mounting options
- \* Continuous air over
- \* Class B insulation

### Specifications

Models	Power		Volts.	Amps.	Frec. Hz.	Protection	Dimensions (mm.)			Leads lenght (mm.) E
	W	H.P.					A	B	C	
REV8105	37	1/20	115	1,00	60	Non Protection	78	16	25,4	550
REV8106	37	1/20	220	0,49	60	Non Protection	78	16	25,4	550
REV8107	50	1/15	115	1,24	60	Non Protection	85	30	31,8	550
REV8108	50	1/15	220	0,56	60	Non Protection	85	30	31,8	550
REV8202	75	1/10	115	1,70	60	Thermal	91	25	38,1	85

### Plane

