



## Shaded pole motor 3,3" (85 x 85 mm). For refrigeration, extraction and ventilation.

### Features

- \* Shaded pole motor / 4 poles
- \* 1550 R.P.M.
- \* Volts 115 - 127 - 220 - 240 - 277 480 VAC
- \* Aluminium endshields
- \* Self-aligning sleeve bearing lubricated with Permaxick® (-45°C a 200°C)

- \* Optional clockwise shaft end rotation (CWSE)
- \* Multiple mounting options
- \* Continuous air over
- \* Silent operation
- \* Totally enclosed
- \* 50 Hz Available

- \* UL recognized motors
- \* High mechanical resistance fan driver
- \* Operating ambient temperature -45°C a +50°C
- \* Class B insulation

### Specifications

Models	Power		Volts.	Amps.	Frec. Hz.	Protection	Dimensions (mm.)				Leads lenght (mm.) E
	W	H.P.					A	B	C	D	
REV-3001	5	1/150	115	0,36	60	Impedance	66	16	12,7		550+/-10
REV-3051	5	1/150	220	0,18 / 0,16	50 / 60	Impedance	66	16	12,7		550+/-10
REV-3101	7	1/100	115	0,60	60	Non Protection	72	16	19,0	10,0	550+/-10
REV-3151	7	1/100	150	0,20	60	Non Protection	72	16	19,0	10,0	550+/-10
REV-3201	10	1/70	115	0,62	60	Non Protection	72	16	19,0	10,0	550+/-10
REV-3251	10	1/70	220	0,34 / 0,31	50 / 60	Non Protection	72	16	19,0	10,0	550+/-10
REV-3301	12	1/62	115	0,80	60	Thermal	72	16	19,0	10,0	550+/-10
REV-3351	12	1/62	150	0,36	60	Thermal	72	16	19,0	10,0	550+/-10
REV-3401	18	1/40	115	1,01	60	Thermal	78	16	25,4	15,5	550+/-10
REV-3451	18	1/40	220	0,55 / 0,50	50 / 60	Thermal	78	16	25,4	15,5	550+/-10
REV-2401	18	1/40	115	1,01	60	Non Protection	78	16	25,4	15,5	550+/-10
REV-2412	18	1/40	115	1,00	60	Non Protection	72	16	19,0	10,0	230+/-10
REV-6501	22	1/34	115	1,00	60	Thermal	85	30	31,8	15,5	550+/-10
REV-6551	22	1/34	220	0,53	60	Thermal	85	30	31,8	15,5	550+/-10
REV-6603	34	1/22	110	1,40	60	Thermal	91	27	38,1	15,5	550+/-10
REV-6652	34	1/22	220	0,65	60	Thermal	91	27	38,1	15,5	550+/-10

### Plane

